

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>C02F 1/68</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 96/40592</b> <b>(43) International Publication Date:</b> 19 December 1996 (19.12.96)
<b>(21) International Application Number:</b> PCT/US96/08308 <b>(22) International Filing Date:</b> 3 June 1996 (03.06.96) <b>(30) Priority Data:</b> 08/474,583 7 June 1995 (07.06.95) US <b>(71) Applicant:</b> MONSANTO COMPANY [US/US]; 800 N. Lindbergh Boulevard, St. Louis, MO 63167 (US). <b>(72) Inventor:</b> SMITH, Lowell, R.; 1750 Kimkirk Court, Kirkwood, MO 63122 (US). <b>(74) Agent:</b> SZCZEPANSKI, Steven, Z.; P.O. Box 4433, Houston, TX 77210-4433 (US).		<b>(81) Designated States:</b> AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> FORMIC ACID AND FORMALDEHYDE DESTRUCTION IN WASTE STREAMS		
<b>(57) Abstract</b> <p>A process is provided for destroying formic acid and/or formaldehyde in an aqueous, organic acid waste stream by contacting the stream with a supported precious metal catalyst and passing air or molecular oxygen gas through the solution to promote chemical oxidation. The invention is a safe, practical and cost effective alternative to bio-system treatment of these compounds using microorganisms. The process of the invention may be practiced in either a batch or continuous mode and, in accordance with the invention, formic acid present in a stream at a level of 3800 ppm and formaldehyde present in an amount of 5800 ppm can be reduced respectively to levels of 200 ppm or less.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

FORMIC ACID AND FORMALDEHYDE DESTRUCTION  
IN WASTE STREAMS

5 BACKGROUND

Field Of The Invention

This invention involves the efficacious treatment of an aqueous stream containing governmentally regulated  
10 formic acid and/or formaldehyde.

More particularly, this invention relates to a process for destroying formic acid and/or formaldehyde in an aqueous waste stream by precious metal-catalyzed oxidation.

15

Description Of The Related Art

It is believed that the present invention can be practiced, generally, in conjunction with aqueous streams containing formic acid and/or formaldehyde.

20 Given its potential for broad application, the present invention has been shown to have particular advantageous application in treating the formic acid and formaldehyde-containing waste stream generated in connection with the manufacture of N-phosphonomethyl-  
25 glycine.

N-phosphonomethylglycine, which is known in the agricultural chemical industry as glyphosate or glyphosate acid, is a highly effective and commercially important herbicide useful in controlling the growth of  
30 germinating seeds, emerging seedlings, maturing and established woody and herbaceous vegetation, and aquatic plants.

Glyphosate and its salts are conveniently applied in an aqueous formulation as a broad-spectrum  
35 (i. . effective on a wide variety of plants), post-emergent herbicide.

- 2 -

(i.e. effective on a wide variety of plants), post-emergent herbicide.

Various methods are known in the art for the preparation of N-phosphonomethylglycine and its  
5 intermediate composition N-phosphonomethylimino-diacetic acid.

For example, in U.S. Patent No. 4,724,103 to Gentilcore a process for preparing N-phosphonomethyl-  
iminodiacetic acid (glyphosate intermediate) is  
10 disclosed. This process involves sequentially reacting an alkali metal salt of iminodiacetic acid with a strong mineral acid to form the strong mineral acid salt of iminodiacetic acid and the alkali metal salt of the  
15 strong mineral acid and phosphonomethyl-ating the iminodiacetic acid by reaction with formaldehyde and phosphorous acid to provide a mixture of N-phosphonomethyliminodiacetic acid and an alkali metal salt.

Also involved in the process is a step by which  
20 the desired intermediate product is separated from other reaction products leaving a formaldehyde-containing waste solution that is readily treatable in accordance with the process of the present invention when formaldehyde and formic acid are distilled out of the  
25 heavy organic waste stream by overhead evaporation.

In U.S. Patent No. 3,969,398 to Hershman, a process is disclosed for the production of N-phosphonomethylglycine by the oxidation of N-phosphonomethyliminodiacetic acid utilizing a  
30 molecular oxygen-containing gas as the oxidant in the presence of a catalyst comprising activated carbon.

Characteristic of glyphosate production, such as in this process, there is often provided a conventional distillation step whereby a formic acid and  
35 formaldehyde-containing overhead waste stream is formed when these undesirables are separated from the

- 3 -

desired N-phosphonomethylglycine product as by distillation.

The liquid waste stream thus formed is a solution containing significant amounts of formaldehyde and formic acid which are substances that cause toxicological concern and are suspected carcinogens.

Eliminating the formaldehyde and formic acid from this stream in high yields is, thus, desirable.

The present invention provides a technically simple and direct process, whereby substantially all of the formic acid and formaldehyde in an aqueous organic stream and, particularly, in waste streams obtained in connection with the production of N-phosphonomethyliminodiacetic acid (i.e. glyphosate intermediate) and N-phosphonomethylglycine or glyphosate acid are eliminated.

This disproportionately high oxidation/conversion of formaldehyde into formic acid and formic acid, in turn, to carbon dioxide and water occurs surprisingly fast and efficiently in connection with the process of the present invention.

#### SUMMARY OF THE INVENTION

In accordance with the practice of the present invention, an aqueous waste stream containing unreacted formic acid and/or formaldehyde is treated by oxidation catalyzed by a supported precious metal catalyst.

In a particular embodiment formaldehyde and formic acid, each present in a representative aqueous waste stream in respective amounts of approximately 6000 ppm and 4000 ppm, are generated from the manufacture of N-phosphonomethylglycine by the reaction of N-phosphonomethyliminodiacetic acid, water and oxygen. In accordance with the invention disclosed herein, these materials are each substantially eliminated and reduced to a commercially innocuous and acceptable level of 200

- 4 -

ppm or less in which case the stream is rendered suitable for recycling.

The novel and useful method of the present invention is amenable for being practiced in either a batch format or as a continuous process. Further, while various supported metal catalysts may be employed in the practice of the invention and particularly those supported catalysts containing any one of the metals selected from Group VIII as contained in the Periodic Table of Elements, a heterogeneous Pt on carbon catalyst is the preferred catalyst for carrying out the process of the invention.

Adherence to certain process variables in accordance with the invention including temperature, pressure and the level of dissolved air or oxygen in the solution being treated is also important in obtaining maximum advantage from the invention.

When compared to the alternative bio-treatment of undesirable formaldehyde and/or formic acid, several significant advantages are believed to inure to the process of the present invention. In particular, catalytic oxidation of these undesirables is considered less capital intensive. Also, it avoids the generation of bio-sludge and, very significantly, where evaporator overhead streams are treated in accordance with the present invention, a substantially undesirable-free aqueous stream can be generated suitable for recycling back through the original process.

30

#### DETAILED DESCRIPTION OF THE INVENTION

As indicated above, the present invention may be practiced in conjunction with eliminating formaldehyde and formic acid, generally, from aqueous organic streams.

- 5 -

However, because these undesirable compounds are produced in connection with the manufacture of N-phosphonomethylglycine, and because the present invention has been found to be particularly useful in  
5 treating waste streams produced in connection therewith, reference will be made to an embodiment of the invention in which formaldehyde and formic acid are destroyed in effluent from the production of N-phosphonomethylglycine. Thus, it is in this context that the  
10 description below will fully disclose the invention and describe its mode of operation with particularity.

Considerable quantities of formic acid and formaldehyde are generated as waste products, for example, in the manufacture of N-phosphonomethylglycine. The destruction of formic acid and/or  
15 formaldehyde in waste streams is required to reduce the emissions of these potentially toxic and governmentally regulated materials.

Presently, these compounds are typically  
20 separated from process streams by either evaporation or ion exchange and then destroyed in bio-treatment facilities using biological treatments such as by microorganisms.

A waste stream containing undesirably high levels  
25 of formaldehyde and formic acid which the practice of the present invention converts into environmentally acceptable products is generated by the practice of the processes disclosed in U.S. Patent Nos. 4,724,103 and 3,969,398.

30 In the former process, disodium iminodiacetate (DSIDA) and phosphorus trichloride ( $\text{PCl}_3$ ) are heated together in water to an elevated temperature to yield a slurry of the hydrochloride of iminodiacetic acid, sodium chloride and phosphorous acid. Thereafter,  $\text{CH}_2\text{O}$   
35 (as formalin) is slowly added. The resulting reaction mixtur is cooled. An aqueous solution of sodium

- 6 -

hydroxide is then added in an amount sufficient to minimize the solubility of N-phosphonomethyliminodiacetic acid which precipitates from solution. The mixture is filtered or centrifuged and the resulting solid material is recovered. The resulting liquid from the isolation of N-phosphonomethyliminodiacetic acid is a waste stream containing, among other things, potentially toxic formaldehyde and formic acid, selected organic phosphonic acids, sodium chloride and selected mineral acids of phosphorus.

When undesirable formaldehyde and formic acid are distilled out of this heavily organic stream such as by distillation to form a second waste stream, the practice of the present invention converts the second formaldehyde and formic acid-containing stream into a predominant mixture of environmentally benign carbon dioxide and water. Thus, the stream is rendered more suitable for either disposal or, where an overhead stream is treated, for recycling back through the underlying process.


In accordance with the process of the present invention formaldehyde and/or formic acid are catalytically oxidized and, thus, eliminated from aqueous waste streams containing these undesirable compounds.

Catalytic oxidation as carried out in accordance with the process of the invention involves the treatment of a formaldehyde and/or formic acid-containing aqueous stream with a supported metal catalyst in the presence of dissolved oxygen or oxygen-containing air.

The preferred catalyst support material is carbon and the metal for loading in the catalyst is selected from among the Group VIII metals. Further, the basic chemistry involved in the process is as follows:



- 7 -



Reaction 1 shows that, when oxidized in  
5 accordance with the present invention, formaldehyde  
converts to formic acid and reaction 2 shows that formic  
acid, in turn, is converted to environmentally benign  
carbon dioxide and water.

In a broad sense, the reactions shown above may  
10 be practiced in accordance with the present invention in  
any conventional reactor at room temperature and  
atmospheric pressure. Furthermore, provided that a  
suitable level of oxygen or oxygen-containing air is  
dissolved in the stream being treated, any of the Group  
15 VIII metals may be employed in the practice of the  
invention.

In order to obtain the maximum advantage from  
the invention, however, and to make it particularly  
useful in a commercial context the adherence to certain  
20 process limitations in accordance with the invention is  
required.

In this regard, while any conventional reactor  
system may be employed to practice the invention, one  
suitable for pressurized operation and having a good  
25 agitation character is preferred. These features of the  
suitable reactor will enable the invention to be  
practiced more efficiently because agitation and  
pressure facilitate the dissolution of oxygen or oxygen-  
containing air into the waste stream - the concentration  
30 of which affects catalytic activity as alluded to above.

In a similar manner, the choice of the particular  
Group VIII metal and the amount of its loading to the  
carbon support or substrate will also affect the rate of  
the oxidation reaction and, thus, the relative  
35 commercial advantage obtained in practicing the  
invention. The inventor has discovered that, from the

- 8 -

Group VIII metals, palladium (Pd), rhodium (Rh) and particularly platinum (Pt) function most desirably in conjunction with the invention. For this reason, platinum is the preferred metal loading for the catalyst and is, therefore, referenced in the data that comprise this disclosure.

The catalyst may contain platinum in the range of about 0.1 wt.% to about 10 wt.% as long as the total ratio of platinum to the working reactor volume is in the range of about 0.00015 to 1 up to about 0.00040 to 1.

Those skilled in the art will recognize that, while the remaining group VIII metals may be employed in this invention, they will lead to slower reaction rates unless employed in larger amounts.

Those skilled in the art will appreciate that comparatively high loadings of the selected metal in the catalyst are likely to result in an improved degree and rate of reaction and, thus, may be preferred over lower loadings. The cost of the catalyst, however, is often a factor in its selection and, where as here, the preferred metal loading is comprised of a precious and expensive metal such as platinum an obvious advantage exists in identifying optimum catalyst loadings for use in the present invention. Thus, based upon the teachings provided herein, those skilled in the art will be able to determine such optimal catalyst. A compromise must be made between practical reaction rates and catalyst cost.

As indicated above, a suitable reactor for use in conjunction with the present invention should have a good agitation feature. Agitation is instrumental in aiding the dissolution of oxygen which is critical to the successful practice of the invention. For example, it has been found that when the concentration of dissolved oxygen is too low, incomplete reaction occurs.

- 9 -

Surprisingly, and obversely, too high a concentration of dissolved oxygen is also deleterious to the process of the invention. More specifically, it has been found that the optimum dissolved concentration of oxygen is in the range of about 1-7 ppm. When the process of the invention is operated having a dissolved oxygen concentration outside these limits, in the case of continuous mode - the oxidation reaction is not completed and in the batch mode a longer time is required to complete the reaction. Thus, it is clear that to ensure this concentration of dissolved oxygen in accordance with the process of the invention, the interaction between oxygen and/or oxygen contain air flow rate and agitation must be considered.

An analysis of a typical waste stream such as one obtained from the manufacture of N-phosphonomethylglycine prior to treatment in accordance with one embodiment of the present invention is as follows:

<u>Component</u>	<u>Weight Percent</u>
Water	99.1
Formic acid	0.4
Formaldehyde	0.6

#### EXAMPLES 1 - 3

The process described above was carried out under a variety of reaction conditions with various waste streams having been obtained from the production of N-phosphonomethylglycine generally in accordance with the process of U. S. Patent No. 3,969,398. Each waste stream contained relative concentrations of formaldehyde and formic acid of approximately 6000 ppm/0.6 wt% and approximately 4000 ppm/0.4 wt.% respectively. The stream temperature while in the reactor varied from about 50° C to about 90° C. The concentrations of formaldehyde and formic acid in the streams before and

- 10 -

after each treatment were noted. The data from representative testing have been tabulated below.

All tests were performed in a continuous mode for up to 30 hours. The catalyst employed in these tests was 1.659g of a Degussa F199XKYA/W, assaying at 4.49 wt.% Pt equivalent to 32 mg of Pt. Reactor volume was 120g. and reactor pressure was 100 psi. Reactor temperature was maintained at 90° C and the liquid feed rate was 6.0 g/min. The oxygen feed rate was 100cc/min. and agitator speed was 1000 rpm. Data were collected every hour to ensure steady state conditions were maintained during the tests. An in-line FTIR was utilized for measuring the concentrations of formaldehyde and formic acid during the course of each run. It can be appreciated by those skilled in the art that this process can be readily scaled up for commercial use without loss of its advantages or efficiency.

Table 1

	Length of run (Min.)	Effluent Formaldehyde, ppm Average Conc.	Formaldehyde End Conc. in ppm
	1. 1728	32	0
	2. 1205	41	18
25	3. 821	51	0

The average formaldehyde effluent concentration, as indicated in the above Table 1 was calculated by averaging all of the formaldehyde concentration data compiled throughout the duration of the test run.

Based upon experimentation, it was observed that formic acid effluent concentrations were lower than formaldehyde concentrations. Thus, formic acid concentrations were not routinely analyzed.

- 11 -

The information above is illustrative of the efficient manner in which the present invention may be operated continuously. However, the process of the invention may also be performed advantageously under  
5 batch conditions.

For example, in one autoclave reactor having a working volume of 120 ml., a slurry of 0.4 wt% of a 5 wt.% Pt. on carbon catalyst oxidized 5800 ppm of formaldehyde and 3800 ppm of formic acid in a solution  
10 to trace levels within 35 minutes or less. Temperatures during the reactions ranged from about 55°C - 90°C and pressure was either 100 or 150 psig. Oxygen flow rates were 25 or 100 cc/min. Surprisingly, the greatest rate differences were observed in connection with oxygen flow  
15 rate changes rather than with changes in temperatures or pressure.

The *in-situ* chemical conversion of the formaldehyde into formic acid and formic acid, in turn, to carbon dioxide and water as provided by the practice  
20 of the present invention has proved to be a most cost effective alternative to bio-treatment elimination of formaldehyde and/or formic acid from aqueous waste streams.

Due to the catalytic nature of the reaction, a  
25 continuous-mode process requiring a relatively short residence time of about 20 minutes has been demonstrated to be technically feasible for the destruction of substantially all of the formaldehyde and formic acid to form environmentally benign carbon dioxide and water in  
30 an aqueous solution suitable for recycling.

The environmental compatibility of the product resulting from the practice of the present invention has thus, been demonstrated.

While the illustrative embodiments of the  
35 invention have been described with particularity, it will be understood that various other modifications will

- 12 -

be apparent to and can be readily made by those skilled in the art without departing from the spirit and scope of the invention.

Accordingly, it is not intended that the scope of  
5 the claims appended hereto be limited to the examples  
and description as set forth hereinabove but rather that  
the claims be construed as encompassing all the features  
of patentable novelty which reside in the present  
invention, including all features which would be treated  
10 as equivalents thereof by those skilled in the art to  
which the invention pertains.

- 13 -

## CLAIMS

WHAT WE CLAIM IS:

5

1. A method for selectively destroying formaldehyde and formic acid undesirable in an aqueous stream comprising the steps of:

- (a) contacting said stream with a metal-  
10 supported catalyst wherein the metal is selected from the group consisting of Group VIII metals; and  
(b) passing air or molecular oxygen through  
said stream in the vicinity of said catalyst thereby  
causing an oxidation reaction which may be continued for  
15 a time sufficient until a desired amount of said  
undesirable are destroyed.

2. The method of claim 1 wherein said  
catalyst is selected from the group consisting of  
20 platinum, palladium and rhodium.

3. The method of claim 1 wherein the  
metal in said metal-supported catalyst is platinum  
loaded on powdered carbon in an amount of about 0.1 wt. %  
25 to about 10 wt. %.

4. The method of Claim 2 wherein said  
reaction is carried out in a suitable reactor at a  
pressure of from atmospheric to about 200 psi and  
30 wherein said stream is heated to a temperature of  
between about 50° C to about 90° C.

5. The method of claim 1 wherein said  
formaldehyde is converted to said formic acid which, in  
35 turn, is converted to carbon dioxide and water.

- 14 -

6. The method of claim 1 wherein in said reaction, a sufficient agitation and oxygen or air flow rate are established such that a level of dissolved oxygen within the range of about 1 ppm to about 7 ppm is  
5 achieved and maintained.

7. A method of treating an acidic aqueous stream containing organic waste comprising formaldehyde, formic acid and other wastes associated with the  
10 manufacture of N-phosphonomethyliminodiacetic acid comprising the steps of:

- (a) subjecting said stream to distillation to form a second stream comprised substantially of formaldehyde and formic acid;
- 15 (b) contacting said second stream with a metal-supported catalyst wherein the metal is selected from the group consisting of Group VIII metals; and
- (c) passing air or molecular oxygen through said stream in the vicinity of said catalyst until a  
20 desired amount of said undesirable are destroyed.

8. The method of claim 7 wherein said catalyst is selected from the group consisting of platinum, palladium and rhodium.  
25

9. The method of claim 7 wherein the metal in said metal-supported catalyst is platinum loaded on powdered carbon in an amount of about 0.1 wt.% to about 10 wt.%.  
30

10. The method of Claim 7 wherein said reaction is carried out in a suitable reactor at a pressure of from atmospheric to about 200 psi and wherein said stream is heated to a temperature of  
35 between about 50° C to about 90° C.

- 15 -

11. The method of claim 7 wherein said formaldehyde is converted to said formic acid which, in turn, is converted to carbon dioxide and water.

5 12. The method of claim 7 wherein in said reaction, a sufficient agitation and oxygen or air flow rate are established such that a level of dissolved oxygen within the range of about 1 ppm to about 7 ppm is achieved and maintained.

10

13. A method of treating an aqueous stream containing formaldehyde and formic acid wastes associated with the manufacture of N-phosphonomethylglycine comprising the steps of:

- 15 (a) contacting said second stream with a metal-supported catalyst wherein the metal is selected from the group consisting of Group VIII metals; and  
(b) passing air or molecular oxygen through said stream in the vicinity of said catalyst until a  
20 desired amount of said undesirable are destroyed.

14. The method of claim 13 wherein said catalyst is selected from the group consisting of platinum, palladium and rhodium.

25

15. The method of claim 13 wherein the metal in said metal-supported catalyst is platinum loaded on powdered carbon in an amount of about 0.1 wt.% to about 10 wt.%.

30

16. The method of Claim 13 wherein said reaction is carried out in a suitable reactor under a pressure of from atmospheric to about 200 psi and wherein said stream is heated to a temperature of  
35 between about 50° C to about 90° C.

- 16 -

17. The method of claim 13 wherein said formaldehyde is converted to said formic acid which, in turn, is converted to carbon dioxide and water.

5 18. The method of claim 13 wherein said reaction is carried out in a suitable reactor at a pressure ranging from atmospheric to about 200 psi.

10 19. The method of claim 13 wherein in said reaction, a sufficient agitation and oxygen or air flow rate are established such that a level of dissolved oxygen within the range of about 1 ppm to about 7 ppm is achieved and maintained.

15 20. The process of claim 15 wherein the product of said reaction is without further treatment in an environmentally acceptable manner.

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US96/08308

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : C02F 1/68

US CL : 210/762, 763, 908; 423/437R

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 210/762, 763, 908; 423/437R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	CA,A, 539,300 (MOSES ET AL) 09 APRIL 1957, See col. 2, lines 4-14; col. 2, line 49 to col. 3, line 20; and col. 5, line 59 to col. 6, line 1.	1-20
P	US,A, 5,460,734 (BIRBARA ET AL) 24 OCTOBER 1995, See col. 3, line 38 to col. 4, line 1.	1-20
Y	US,A, 5,244,581 (MURPHY), 14 September 1993, See col. 1, lines 25-34.	1-20
Y	US,A, 3,804,756 (CALLAHAN ET AL) 16 APRIL 1974, See col. 1, line 44 to col. 2, lines 25 and col. 3, lines 22 to col. 4, line 28.	7-12
Y	US,A, 5,205,906 (GRUTSCH ET AL) 27 APRIL 1993, See col. 3, line 15 to col. 4, line 20.	7-12

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"G" document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

28 JUNE 1996

Date of mailing of the international search report

19 NOV 1996

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

fw WAYNE A. LANGE

Telephone No. (703) 308-0248

THIS PAGE BLANK (USPTO)